

MORCROS

Adhesives

STOP MOULD

FLEXIBLE WALL GROUT

- Anti-bacterial & Fungal Resistant
- Ideal for Hygiene Critical Areas
- 1-5mm Joints
- Ideal with Glass & Mosaic Tiles
- Power Showers
- Water Resistant
- Mix With Water



Description

Norcros Stop Mould Flexible Wall Grout is a fine, smooth finish grouting material for internal and external tiling joints up to 5mm wide. The inclusion of **Rock-Tite™** polymeric binders make it ideal for use with all types of tile including glass where it has excellent adhesion characteristics. It needs only the addition of water and its high flexural strength makes it ideal for dry lined walls and surfaces subject to vibration and durability such as power showers. The product contains **Norcros Stop Mould Anti Bacterial Fortification** to protect against the build up of mould and the discolouration of grouting typically found in areas where frequent wetting, high humidity and condensation may prevail.

Norcros Stop Mould Flexible Wall Grout is water resistant but is not impervious to the passage of water. In areas of potential water ingress preparation of the sub-surface with **Norcros Wet Seal** should be considered. Where an impervious joint is required **Norcros Super Epoxy Grout** should be used.

Conforms to classification **BS EN 13888 CG2**

Preparation

Tiles should be set before grouting is undertaken. Tile joints should be clean and free of adhesive residues. Seal all porous tiles before grouting commences with a suitable impregnating sealer.

Mixing

Add approximately 3 parts of grout powder to approximately 1 part of clean water and mix to a firm, creamy lump free consistency. The grout will have a pot life of around 1 hour. No further water should be added after the initial mixing.



Application

Apply the grout with a rubber float/ squeegee taking care to fully compress the material into the joints. When the grout has begun to firm up in the joints— but not fully set— all residues should be removed from the face of the tiling with a clean sponge and water. Care should be taken not to over wet the surface and thereby remove or weaken the grouting within the joints. It is imperative to remove residues before the grouting begins to set on the face of the tiles. Work in manageable areas and change the cleaning water frequently. When the grout has set remove any final trace of residues and polish off with a damp cloth.



Coverage

1kg of **Stop Mould Flexible Grout** will cover approximately 4m² of 150mm x 150mm x 6mm wall tiles with 2mm joints or 1.5m² of 20mm x 20mm x 4mm mosaics with 2mm spacing.

Storage

When stored in dry internal conditions between 5°C and 30°C and out of direct sunlight the product has a shelf life of 12 months from date of manufacture.

Technical Advice

For advice on tile installation products call the **Norcros Technical Helpline** on **0870 609 2851**.

Colour Available

White

Coverage Rate

This formula is for use with Norcros Products.

$$\frac{(\text{Width} + \text{Length}) \times \text{Depth} \times \text{Joint} \times \text{S.G.}}{\text{Width} \times \text{Length}} = \text{Kg/m}^2$$

S.G (Specific Gravity) for Norcros Grouts:

Norcros Wall Grouts = 2.0

Norcros Wide Joint Grouts = 1.8

Epoxy = 1.6

i.e. Calculation for a 200mm x 100mm x 6.5mm Wall tile with a 3mm joint width

$$\frac{(200 + 100) \times 6.5 \times 3 \times 2}{200 \times 100} = 0.59\text{kg/m}^2$$

NORCROS ADHESIVES

Harewood Street, Tunstall, Stoke-on-Trent, Staffordshire, ST6 5JZ

Telephone: +44 (0) 1782 524140 Fax: +44 (0) 1782 524141

Website: www.norcros-adhesives.com

Norcros Adhesives is a trading division of H&R Johnson Tiles Ltd

5kg