

# WALL TILING

**NORCROS**  
Adhesives



EU Classification

	CEMENT BASED POLYMER MODIFIED			ADHESIVE		GROUT					READY MIX	
	Mosaic & Marble Fix	Rapid Porcelain Tile Adhesive	Rapid Porcelain & Stone Tile Adh.	Fast Set Tile Adhesive	Wall & Floor Tile Adhesive	Wall Tile Grout	Floor & Wall Grout	Wide Joint Flexible Grout	Super Epoxy	Stop Mould	Tile To Showers	Tile To Walls
EU Classification	C1T	C2F	C2F	C1F	C1T	CG1	CG1	CG2	RG1	CG2	D2T	D1T
Internal	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
External	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Render	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Plaster	✓*	✓*	✓*	✓*	✓*	✓	✓	✓	✓	✓	✓	✓
Plaster Board	✓*	✓*	✓*	✓*	✓*	✓	✓	✓	✓	✓	✓	✓
Existing Tiles	✓□	✓□	✓□	✓+	✓+	✓	✓	✓	✓	✓	✓	✓
Backer Board	✓+	✓	✓	✓+	✓+	✓+	✓+	✓	✓	✓	✓	✓
Painted Surfaces	✓**+	✓*	✓*	✓**+	✓**+	✓	✓	✓	✓	✓	✓	✓
Brickwork	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Blockwork	✓**+	✓*	✓*	✓**+	✓**+	✓	✓	✓	✓	✓		
MDF						✓+	✓+	✓	✓	✓	✓	
Plywood Walls	✓+			✓+	✓+	✓+	✓+	✓	✓	✓	✓	



The colours shown are for guidance only. Some variation between the printed colours and the actual grout colours may be expected.

### GROUT COVERAGE RATE

**This formula is for use with Norcros Products.**

$$\frac{(\text{Width} + \text{Length}) + \text{Joint} \times \text{Depth} \times \text{Specific Gravity}}{\text{Width} \times \text{Length}} = \text{Kgs/m}^2$$

Specific gravity for Norcros Grouts:

Norcros Wide Joint = 1.8  
Standard Joint = 2.0  
Epoxy = 1.6

i.e. Standard calculation for 150mm x 150mm (tile size) x 6mm (joint depth) x 3mm (joint width)

$$\frac{(150 + 150) \times 3 \times 6 \times 2}{150 \times 150} = \frac{10800}{22500} = 0.48\text{kg/m}^2$$

\* = USE WITH NORCROS PRIME BOND

▲ = CHECK WITH MANUFACTURER

+ = USE WITH NORCROS ADIFLEX

□ = USE WITH SLURRY BONDING COAT

